

## For Water Heater and Hot Water Storage Tank Applications

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

# Series DET

## Potable Water Expansion Tanks

Series DET Potable Water Expansion Tanks are designed to absorb the increased volume of water created by thermal expansion and to maintain balanced pressure throughout the potable water supply system.

Heated water expands, and in a domestic hot water system the system may be closed when the potable water system is isolated from the public water supply by a one-way valve such as pressure reducing valve, backflow preventer or check valve. Provisions must be made for this expansion.

Series DET expansion tanks absorb the increased volume of water created when the hot water storage tank is heated and keeps the system pressure below the relief setting of the T&P relief valve.

It is a pre-pressurized steel tank with an expansion membrane that prevents contact of the water with the air in the tank. This prevents loss of air to the water and insures long and trouble-free life for the system. These tanks may be used with all types of Direct Fired Hot Water Heaters (gas, oil or electric) and hot water storage tanks.

### Features

- Rugged flexible butyl diaphragm
- Field adjustable pre-charge
- In-line and free standing models
- Can be used with most standard hot water heaters and storage tanks

### Models

DET-5-M1 has 3/4" male connection, tank volume 2.1 gal.

DET-12-M1 has 3/4" male connection, tank volume 4.5 gal.

DET-20-M1 has 3/4" male connection, tank volume 8.5 gal.

DET-35-M1 has 1" female connection, tank volume 14.00 gal.

### Specifications

The potable water expansion tank shall be of drawn steel construction. It shall have a Butyl diaphragm separating the air chamber from the water containing chamber. Inlet connector shall be brass (Model DET-35-M1: Stainless Steel). Materials of manufacture for the diaphragm shall be FDA approved.

The potable water expansion tank shall be a Watts Model DET-\_\_\_\_M1.



### Standards

Models DET-5-M1, DET-12-M1 and DET-20-M1 are Listed by IAPMO.

Certified to ANSI/NSF 61

Model DET-35-M1

Certified to ANSI/NSF 61



(73°F/23°C)

**Note:** The potable water expansion tank shall be installed in the cold water service pipe line on the supply side of the water heater (or water storage tank). A pressure relief valve sized and installed in accordance with local codes must be incorporated in the system. In those systems requiring a combined temperature and pressure safety relief valve, the temperature and pressure relief valve should be sized and installed in accordance with local codes. Adequate drainage provisions should be provided where water flow will cause damage.

See chart on back





## Selection

This Quick Reference Selection Guide may be used as an alternative to using a formula to determine the correct expansion tank for the system. This table is based upon a relief valve setting of 150psi (10.3 bar), and a maximum of 50°F temperature rise.

To select the correct model DET series tank, simply go the supply pressure equal to the system supply pressure (for pressures between those shown use next highest supply pressure shown), read across the chart to the correct tank as indicated by the water heater capacity (for capacities between those shown, use next highest capacity).

To accommodate the thermal expansion required for higher temperature and/or higher pressure systems, multiple tanks may be used. Please contact the factory for sizing information.

SUPPLY PRESSURE (PSIG)	WATER HEATER (GALLONS)						
	20	30	40	50	80	100	120
40							
50							
55							
60							
70							
80							
90							
100							
110							
120							

	DET-5-M1		DET-20-M1
	DET-12-M1		DET-35-M1
	Multiple tanks required - consult factory		

## Materials

Diaphragm: Butyl rubber


Inlet Connection: Brass (DET-35-M1: Stainless Steel)

## Technical Information

Description	DET-5-M1	DET-12-M1	DET-20-M1	DET-35-M1
Max. Pressure - PSI	150	150	150	150
Max. Temp. - °F	200	200	200	200
Tank Volume - Gal.	2.1	4.5	8.5	14.00
Tank Acceptance - Gal.	.85	1.8	3.2	5.6
Air Pre-charge - PSI	20	20	20	20
Connections Size - Inches	¾ Male	¾ Male	¾ Male	1 Female
Diameter - Inches	8.5	10.0	12.5	16.0
Length - Inches	11.5	15.0	19.2	21.7
Weight - Lbs.	7	10	15	32

## Acceptance Volume

Air Side Pre-pressure (psi)	Water Side Volume at 150psi (gallons)			
	DET-5-M1	DET-12-M1	DET-20-M1	DET-35-M1
20	1.500	2.801	7.102	10.69
40	1.272	2.208	5.882	9.17
60	.996	2.076	4.705	7.59
80	.720	1.716	4.009	6.07



Water Safety & Flow Control Products



ISO 9001-2000 CERTIFIED

USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com

Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca